SONY
make.believe

2 International Business Park #05-10 Tower One The Strategy Singapore 609930
Telephone: (65) 6544 8338 Facsimile: (65) 6544 8330

Specifications Sheet

	MDR-EX1000	MDR-EX600	MDR-EX510SL	MDR-EX310SL
TYPE	Closed Dynamic			
DRIVER UNIT	16mm diameter, dome type (CCAW adopted)		13.5mm diameter, dome type (CCAW adopted)	
SENSITIVITY	108 dB/mW	107 dB/mW	106 dB/mW	105 dB/mW
IMPEDENCE	32 Ω @ 1 KHz		16 Ω @ 1 KHz	
MAGNET	Neodymium			
FREQUENCY RESPONSE (Hz)	3 - 30,000 Hz	4 - 28,000 Hz	5 - 27,000 Hz	5 - 25,000 Hz
POWER HANDLING CAPACITY	200mW (IEC)			100mW (IEC)
CORD	1.2m/0.6m 7N-OFC Litz cord, Y-type, detachable		0.6m OFC Litz cord, neck-chain	
SUPPLIED ACCY	Hybrid silicone rubber earbuds SS(2), S(2), MS(2), M(2), ML(2), L(2), LL(2) / Noise isolation earbuds S(2), M(2), L(2) / 1.2m cord / 0.6m cord / Carrying case / Product information	Hybrid silicone rubber earbuds SS(2), S(2), MS(2), M(2), ML(2), L(2), LL(2) / Noise isolation earbuds S(2), M(2), L(2) / 1.2m cord / 0.6m cord / Carrying case	Hybrid silicone rubber earbuds SS(2), S(2), M(2), L(2) / Noise isolation earbuds S(2), M(2), L(2) / Extension cord (90cm) / Cord adjuster / Carrying pouch	
WEIGHT	Approx. 8g (without cord)		Approx. 7g (without cord)	